



# THE BASICS

BASIC COATINGS • PO BOX 677  
DES MOINES, IA 50303 • 800-441-1934

## IFT - Intensive Floor Treatment TYPICAL PROPERTIES AND APPLICATION PROCEDURES

### PRODUCT DESCRIPTION

IFT is the first step in a two-part cleaning system designed to prepare floors for the application of TyKote® as the correct floor preparation process when using Basic Coatings TyKote System. IFT is a powerful cleaner designed to remove tough oil, dirt and other residue from the floor as preparation for the recoating process. IFT is a vital part of the preparation process for Basic Coatings TyKote System and should never be omitted when used to prepare surfaces for Basic Coatings TyKote System application.

### TYPICAL PROPERTIES

Color	Lavender (light purple)
Density	8.30-8.40 lbs./gallon
PH	12-14
VOC	At minimum dilution does not exceed 2% by weight
Flash Point	Greater than 200°F
Freeze/Thaw Stability	Stable

### APPLICATION METHOD

1. To prepare the floor for the cleaning process, remove all caked mud, chewing gum and other debris from the floor. Vacuum the dirt from the floor. Pay special attention to corners.
2. IFT should be diluted using a ratio of 4 parts water to 1 part Intensive Floor Treatment.
3. Soak several clean towels in the solution and wring them until nearly dry. Rubber gloves must be worn to protect hands from skin irritation.
4. Wrap a towel around a push broom and tack the floor. To prevent redeposit of dirt and oil, refold towel using clean sides as needed. Pay special attention to corners.
5. Repeat steps 3-4 in each area of the floor until the entire floor has been cleaned.
6. **NOTE:** For stubborn surface marks, dirt and shoe marks, use a moderately abrasive nylon pad or sponge moistened with IFT and scour area manually until spot is removed. Follow with a clean water rinse on scrubbed area.
7. Always rinse the floor by damp mopping with **clean water** and a clean mop until the rinse water is clean or use tack towels with clean water. Pay special attention to corners.
8. Clean the floor again using Squeaky Cleaner, following the same cleaning procedure described above. (Steps 2-4) Since Squeaky Cleaner does not leave a residue, no clear water rinse is needed after this step. The two cleaners are specifically formulated to remove different types of contaminants from the floor and may not be combined into a single treatment.

### ALTERNATE APPLICATION METHOD

1. Prepare a diluted solution of IFT using 4 parts water to 1 part IFT in a mop bucket.
2. Soak string mop in the solution and wring excess out.
3. Mop the floor paying special attention to corners. Re-soak and wring mop frequently. Mop until the entire floor has been cleaned.
4. Always rinse the floor by damp mopping with **clean water** and a clean mop until the rinse water is clean or use tack towels with clean water. Pay special attention to corners.
5. Clean the floor again using Squeaky Cleaner, following the same cleaning procedure described above. Since Squeaky Cleaner does not leave a residue, no clear water rinse is needed after this step. The two cleaners are specifically formulated to remove different types of contaminants from the floor and may not be combined into a single treatment.

**AUTO-SCRUBBER APPLICATION METHOD**

1. If using an automatic scrubber, use a dilution rate of 4 parts water to 1 part Intensive Floor Treatment along with a white, red, brown or black pad. Make sure squeegees and buffing pads work well. A person with a mop must follow behind the scrubber to pick up any water that is not picked up from the machine. Pay special attention to corners.

**PACKAGING**

Gallons, 2-2 1/2 gallons (buddy packs)

**OBLIGATION OF MANUFACTURER/SELLER**

The following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss of damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, the user shall determine the suitability of the product for the intended use and user assumes all risk and liability whatsoever in connection therewith. The foregoing may not be altered except by an agreement signed by officers of seller and manufacturer.